

22000 MOUNT SERIES

Low-profile, high capacity mounts for vibration and shock protection.

APPLICATIONS

- Truck, bus and marine engines
- Generators
- HVAC equipment
- Electronic equipment
- Truck cabs
- Machinery, pumps & compressors

FEATURES

- Fail-safe when used with snubbing washer
- Axial to radial stiffness of 1:1
- Low natural frequency
- Sturdy, reliable construction

BENEFITS

- Economical
- Bonded construction provides constant performance characteristics
- Overlapping load ranges

LOAD RANGE

- 5 sizes with 25 load ratings to 4,560 lbs. per isolator



22000 Series mounts are designed to withstand the rigors of heavy-duty vehicular applications, off-the-road equipment, large trucks and construction equipment. The standard neoprene elastomer is resistant to oil. Other materials are available on special order.

Specifications

• Natural Frequency	8-18 Hertz
• Transmissibility at resonance	8:1
• Resilient Element	Neoprene
• Standard Materials	Sintered metal and cold-rolled steel
• Weight	See dimensional drawings

Environmental Data

- Neoprene elastomer has an operating temperature range of -20°F to +180°F (-30°C to +82°C) and is resistant to oils, most solvents and ozone.
- Special elastomers and finishes are available for applications in severe environments.